

SECTION 122413 WINDOW SHADES

PART 1 - GENERAL

1.1 GENERAL REQUIREMENTS

- A. Work of this Section, as shown or specified, shall be in accordance with the requirements of the Contract Documents.

1.2 SECTION INCLUDES

- A. Work of this Section includes all labor, materials, equipment, and services necessary to complete the window shades as shown on the drawings and/or specified herein, including, but not limited to, the following:
 - 1. Manually-operated window shades.
 - 2. Field measurements of as-built conditions.
 - 3. Accessories and hardware required for complete installation and operation.

1.3 QUALITY ASSURANCE

- A. Provide assemblies that are complete assemblies produced by one manufacturer, including hardware, accessory items, mounting brackets, and fastenings.
- B. Provide materials in colors as selected by the Architect from manufacturer's standard colors.

1.4 SUBMITTALS

- A. Product Data: For each type of product indicated. Include styles, material descriptions, construction details, dimensions of individual components and profiles, features, finishes, and operating instructions.
- B. Shop Drawings: Submit floor layout and elevations, indicating location of all window treatments, mechanism details, type and size of each unit. Shop drawings must also show seaming of shade fabric. Submit shop drawings showing details of installation and relation to adjoining construction and conditions.
- C. Samples: Submit full size sample of each shade type for Architect's acceptance.

1.5 Mock-Up

- 1. Install each type of shade assembly on one complete column bay for Architect's acceptance of installation details, workmanship and operation.
- 2. Approved mock-up shall be used as the standard for installation of work under this Section, and no further installation work shall proceed before Architect's acceptance of the mock-up.

1.6 WARRANTY

- A. Manufacturer's standard non-depreciating 25-year limited warranty covering all hardware, motors, motor control system and shade cloth.

1.7 DELIVERY, STORAGE AND HANDLING

- A. Protect shades from damage, soiling and deterioration during transit, storage and handling to, until Owner's acceptance.

PART 2 - PRODUCTS

2.1 MANUALLY OPERATED SHADES

- A. Provide manually operated shade system equal to "Mechoshade/5 System," made by the Mecho-Shade Corp. or equal made by Sol-R-Veil Inc., Draper, or approved equal conforming to standards specified herein.
- B. Shade system shall be pre-engineered overrunning clutch design that disengages to 90% during the raising and lowering of the shade. The brake can stand a pull force of 40 lb. in the stop position. Requires no adjustment. Self-lubricating hub on to which the brake system is mounted includes an articulated brake assembly which assures smooth, non-jerky operation in raising and lowering the shades. System shall include the following components:
1. Provide shade hardware allowing for the removal of shade roller tube from brackets without removing hardware from opening and without requiring end or center supports to be removed.
 2. Provide shade hardware that allows for removal and remounting of the shade bands without having to remove the shade tube, drive or operating support brackets.
 3. Provide for universal, regular and offset drive capacity, allowing drive chain to fall at front, rear or non-offset for all shade drive end brackets. Universal offset shall be adjustable for future change.
 4. Provide shade hardware system that allows for removable regular and/or reverse roll fascias to be mounted continuously across two or more shade bands without requiring exposed fasteners of any kind.
 5. Provide shade hardware system that allow for operation of multiple shade bands (multi-banded shades) by a single chain operator. Connectors shall be offset to assure alignment from the first to the last shade band.
 6. Provide shade hardware constructed of minimum 1/8" thick plated steel or heavier as required to support 150% of the full weight of each shade.
 7. Drive Bracket/ Brake Assembly:
 - a. MechoShade Drive Bracket M5 or equal by other manufacturers noted herein.
 - b. Drive Chain: #10 qualified stainless steel chain rated to 90 lb.
 - c. Minimum Breaking Strength: Nickel plate chain shall not be accepted.
- C. Shade Bands: Construction of shade band includes the fabric, the hem weight, hem pocket, shade roller tube, and the attachment of the shade band to the roller tube. Sewn hems and open hem pockets are not acceptable.
1. Hem Pockets and Hem Weights: Fabric hem pocket with RF welded seams (including welded ends) and concealed hem weights. Hem weights shall be of appropriate size and weight for shade band. Hem weight shall be continuous inside a sealed hem pocket. Hem pocket construction and hem weights shall be the same, for all shades within one room.
 2. Shade Band and Shade Roller Attachment:

- a. Provide extruded aluminum shade roller tube of a diameter and wall thickness required to support shade fabric without deflection. Provide for positive mechanical engagement with drive/ brake mechanism.
- b. Provide for positive mechanical attachment of shade band to roller tube; shade band shall be made removable/ replaceable with a snap-on/snap-off spline mounting, without having to remove shade roller from shade brackets.
- c. Mounting spline shall not require use of adhesives, adhesive tapes, staples and/or rivets.

2.2 SHADE CLOTH

- A. Solar Shades: Shade cloth shall be "ThermoVeil," 1550 Series, 3% with openness factors indicated below, of weave color selected by the Architect made by MechoShade, or equal by other manufacturers noted herein.
 1. East, West and North Wall: 3% open
 2. South Wall: 1% open
- B. Blackout Shades: Where blackout shades are indicated, shade cloth shall be "Equinox 0100 Series" opaque acrylic black-out shade cloth made by MechoShade, or equal by other manufacturers noted herein; color selected by the Architect.
- C. At Commissioner Meeting Room, Large Training, Conference Rooms (rooms greater than 500 square feet): Provide double shade in these locations, solar shade and blackout shade.

2.3 FABRICATION

- A. The shade and the fabric shall hang flat without buckling or distortion. The edge, when trimmed, shall hang straight without curling or raveling. An unguided roller shade cloth shall roll true and straight, without tracking sideways more than +/- 1/8" in either direction due to warp distortion or weave design. Shades shall fill window openings from head to sill and jamb to jamb.

PART 3 - EXECUTION

3.1 INSPECTION

- A. Examine the areas and conditions where window treatments are to be installed and correct any conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions are corrected to permit proper installation of the work.

3.2 INSTALLATION

- A. In all spaces where base is indicated, install bases tight to walls, partitions, columns, built-in cabinets, etc., without gaps at top or bulges at bottom, with tight joints and flush edges, with molded corner pieces at internal and external corners. Provide end stops adjacent to flush type door frames and where base does not terminate against an adjacent surface. Keep base in full contact with walls until adhesive sets.
- B. General
 1. Coordinate with the work of other trades to assure proper and adequate provision in the work of those trades for interface with the work of this Section.

2. Install the work of this Section in strict accordance with the indicated design and the installation recommendations of the manufacturer as approved by the Architect.
3. Upon completion of the installation, put all components through at least ten (10) complete cycles of operation, adjusting as necessary to achieve optimum operation.

C. Manual Roller Shades

1. Install roller shades level, plumb, square, and true according to manufacturer's written instructions and located so shade band is not closer than 2" to interior face of glass. Allow proper clearances for window operation hardware.
2. Adjust and balance roller shades to operate smoothly, easily, safely, and free from binding or malfunction throughout entire operational range.
3. Clean roller shade surfaces after installation, according to manufacturers written instructions.

3.3 PROTECTION AND CLEANING

- A. Protect installed units to ensure proper operating condition, without damage or blemishes. Repair or replace damaged units as directed by the Architect.

END OF SECTION 122413