

**SECTION 102600 WALL PROTECTION**

PART 1 - GENERAL

1.1 GENERAL REQUIREMENTS

- A. Work of this Section, as shown or specified, shall be in accordance with the requirements of the Contract Documents.

1.2 SECTION INCLUDES

- A. Work of this Section includes all labor, materials, equipment, and services necessary to complete the wall protection as shown on the drawings and/or specified herein.
  - 1. Wall protection sheet.

1.3 RELATED SECTIONS

- A. Gypsum Drywall - Section 092900.

1.4 SUBMITTALS

- A. Product Data: Submit manufacturer's product data and installation instructions for each material and product used.
- B. Samples: Wall protection sheets, 12" square.
- C. Shop Drawings: Submit shop drawings for wall protection showing all anchorage devices.

PART 2 - PRODUCTS

2.1 MATERIALS

- A. Wall Protection: Provide impact-resistant wall covering sheets by Koroseal (Korogard Wall Protection Systems), Acrovyn C/S, IPC, or approved equal.
  - 1. Basis of Design Product: Korogard Protective Wall Covering by Koroseal; decorative high-impact semi-rigid sheet.
    - a. Fire Rating: Class A.
    - b. Thickness: 0.040".
    - c. Color(s): As selected by Architect from manufacturer's standard range.
    - d. Pattern: As selected by Architect from manufacturer's standard range.
    - e. Texture: As be selected by Architect from manufacturer's standard range.
- B. Polycarbonate Plastic Sheet: ASTM D6098, S-PC01, Class 1 or Class 2, abrasion resistant; with a minimum impact-resistance rating of 15 ft.-lbf/in. of notch when tested according to ASTM D256, Test Method A.

**PART 3 - EXECUTION**

**3.1 INSPECTION**

- A. Examine the areas and conditions where wall protection is to be installed and correct any conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions are corrected to permit proper installation of the work.

**3.2 INSTALLATION**

- A. Install wall protection following manufacturer's guidelines.

**3.3 ADJUST AND CLEAN**

- A. Clean surfaces promptly after installation, exercise care to avoid damage to surfaces.
- B. Protect wall protection sheets from damage until acceptance of work.

END OF SECTION 102600