

SECTION 101400 SIGNAGE

PART 1 - GENERAL

1.1 GENERAL REQUIREMENTS

- A. Work of this Section, as shown or specified, shall be in accordance with the requirements of the Contract Documents.

1.2 SECTION INCLUDES

- A. The Work of this Section includes all labor, materials, equipment, and services necessary to complete the signage as shown on the drawings and/or specified herein, including, but not limited to, the following:
 - 1. Room identification signs.
 - 2. Interior directional and door signage.
 - 3. Fire egress, floor, and other signs required by Code.

1.3 RELATED SECTIONS

- A. Display Cases - Section 101200.
- B. Directories - Section 101300.
- C. Panel Signage - Section 101423.
- D. Exit signs - Division 26.

1.4 QUALITY ASSURANCE

- A. For actual installation of the signage, use only personnel who are thoroughly familiar with the manufacturer's recommended methods of installation and who are completely trained in the required skills.

1.5 SUBMITTALS

- A. Product Data: Submit manufacturer's technical data and installation instructions for each type of sign required.
- B. Samples: Submit samples of each sign showing finishes, colors, surface textures and qualities of manufacture and design of each sign component including graphics.
- C. Shop Drawings: Submit shop drawings for fabrication and erection of signage. Include plans, elevations, and large scale details of sign wording and lettering layout. Show anchorage and accessory items. Furnish location template drawings for items supported or anchored to permanent construction.

1.6 PRODUCT HANDLING

- A. Protection: Use all means necessary to protect the materials of this Section before, during, and after installation, and to protect the installed work and materials of all other trades.

- B. Replacements: In the event of damage, immediately make all repairs and replacements necessary.

PART 2 - PRODUCTS

2.1 PANEL SIGNS

- A. Fire egress, floor, and other signs required by Code shall be as follows:
 - 1. Interior Panel Signs: Provide smooth sign panel surfaces constructed to remain flat under installed conditions within a tolerance of plus or minus 1/16 inch measured diagonally from corner to corner, manufactured from 0.050-inch aluminum sheet, framed. Comply with requirements indicated for finishes, colors, designs, shapes, sizes, and details of construction (as selected by the Architect).
 - 2. Engraved Copy: Machine engrave letters, numbers, symbols, and other graphic devices into panel sign on face indicated to produce precisely formed copy, incised to uniform depth. Fill engraved copy with enamel
 - 3. Tactile Characters: Characters and Grade 2 Braille raised 1/32 inch above surfaces, in contrasting color.

PART 3 - EXECUTION

3.1 INSPECTION

- A. Examine the areas and conditions where signage is to be installed and correct any conditions detrimental to the proper and timely completion of the work. Do not proceed with the work until unsatisfactory conditions are corrected to permit proper installation of the work.

3.2 INSTALLATION

- A. Install units and components at the locations directed by the Architect, securely mounted with concealed theft-resistant fasteners. Attach to substrates in accordance with the manufacturer's instructions.
- B. Install level, plumb, and at the proper height. Cooperate with other trades for installation of sign units to finish surfaces. Repair or replace damaged units as directed by the Architect.

END OF SECTION 101400